Network Tool for Direct Printing

Operation Guide



PUBLICATION ISSUED BY:

Olivetti S.p.A. Gruppo Telecom Italia Via Jervis, 77 - 10015 Ivrea (ITALY) www.olivetti.com

Copyright © 2009, Olivetti All rights reserved

The mark affixed to the product certifies that the product satisfies the basic quality requirements.



The manufacturer reserves the right to carry out modifications to the product described in this manual at any time and without any notice.



ENERGY STAR is a U.S. registered mark.

The ENERGY STAR program is an energy reduction plan introduced by the United States Environmental Protection Agency in response to environmental issues and for the purpose of advancing the development and utilization of more energy efficient office equipment.

Your attention is drawn to the following actions which could compromise the conformity attested to above, as well as the characteristics of the product:

- incorrect electrical power supply;
- incorrect installation, incorrect or improper use or use not in compliance with the warnings provided in the User's Manual supplied with the product;
- replacement of original components or accessories with others of a type not approved by the manufacturer, or performed by unauthorised personnel.

All rights reserved. No part of this material may be reproduced or transmitted in any form or by any means, electronic or mechanical, including photocopying, recording or by any information storage and retrieval system, without permission in writing from the Publisher.

Legal and General Information

Notice

Unauthorized reproduction of all or part of this guide is prohibited. The information in this guide is subject to change without notice.

We cannot be held liable for any problems arising from the use of this product, regardless of the information herein.

Regarding Trademarks

Microsoft, Windows and Windows NT are registered trademarks of Microsoft Corporation.

Apple, AppleTalk, Mac, Macintosh, Mac OS and TrueType are registered trademarks of Apple Computer, Inc.

Adobe, Acrobat and Postscript are registered trademarks of Adobe Systems Incorporated.

Novell and NetWare are registered trademarks of Novell, Inc.

HP and PCL are registered trademarks of Hewlett-Packard Company.

Intel, Pentium and Celeron are registered trademarks of Intel Corporation.

Other brand and product names contained in this document are registered trademarks or trademarks of their respective companies.

General Information

When using this utility, the items that can be configured will differ depending on the model of your printing system or multifunctional printer (hereinafter referred to as "printing system").

Examples in this document are described in terms of the Internet Explorer 6.0 and Microsoft Windows XP operating system environment.

Table of Contents

1.	Features 1		
	1.1. What is Network Tool for Direct Printing?	1	
	1.2. System Requirements		
	1.3. Support Language	1	
2.	Installation and Startup	2	
	2.1. Installation		
	2.2. Startup	2	
3.	Printing PDF	3	
	Names and Functions		
	Printing System Settings 6		
ð.	Detailed Settings 10		



1. Features

1.1. What is Network Tool for Direct Printing?

Network Tool for Direct Printing is a utility that allows you to print PDF files downloaded from Internet such as catalog and documents without starting Adobe Acrobat/Reader.

1.2. System Requirements

The Network Tool for Direct Printing operates in the following environment. Verify your environment before installation.

Item	Description
OS	Microsoft Windows 98 SE/Me (Not supported depending on the model) Microsoft Windows NT 4.0 Workstation Service Pack 6 or later [†] (Not supported depending on the model) Microsoft Windows 2000 Professional [†] Microsoft Windows Server 2000/2003 [†] Microsoft Windows XP Home Edition/Professional Edition [†] Microsoft Windows Vista [†]
Web Browser	Microsoft Internet Explorer 5.5 or later
Hardware	A processor equivalent to a Pentium 200 MHz or greater At least 32 MB of free memory At least 4 MB of free hard disk space SVGA (800 × 600, 256 color) or greater

[†] Administrator rights are required for installation.

1.3. Support Language

Network Tool for Direct Printing supports the following languages: Arabic, Brazilian Portuguese, Czech, Danish, Dutch, English, Finnish, Farsi, French, German, Hebrew, Hungarian, Italian, Japanese, Lithuanian, Korean, Norwegian, Polish, Portuguese, Russian, Simplified Chinese, Spanish, Swedish, Traditional Chinese and Turkish.

2. Installation and Startup

2.1. Installation

Install Network Tool for Direct Printing in your computer.

Note

Before installing this utility, make sure that any of the printer drivers are installed. The **Printer Driver** is provided on the CD-ROM supplied with the printing system.

Insert the CD-ROM that came with the printing system into the optical drive of the computer.

The installation program starts up automatically. Follow the instructions for installation.

2.2. Startup


When the installation is completed, you can start the **Network Tool for Direct Printing** by proceeding from the start menu > **All Programs** > **Network Tool for Direct Printing** > **Network Tool for Direct Printing**.



3. Printing PDF

Perform the following procedures below to print PDF file using **Network Tool for Direct Printing**.

1 Start Network Tool for Direct Printing.




- 2 Add the desired PDF files to the **File Name** list by the following methods.
 - Click the Add button to select files from the Open File dialog box.
 - Select the file in Windows explorer and then drag and drop it to the icon for this application (including shortcut).
 - Select the file in Windows explorer and then select Network Tool for Direct Printing in the context menu.
 - Select the file and then drag and drop it to this window.
- 3 Select the printing system to print PDF files from the **Printer Listing** pull-down menu.
- 4 Click the **Settings** button and make settings for printing. For details, refer to *Printing System Settings* on page 6.

Note

When you want to load the previously saved setting, select the setting file from the **User Printer Settings** pull-down menu or click the **Browse** button.

Olick the **Detailed Settings** button and make the detailed settings such as page range for printing and media type. For details, refer to *Detailed Settings* on page 10.

6 Click the **Print** button. The **Confirmation** dialog box appears.




Notes

- Checking Enable Multiple Master Font and then clicking OK enable to generate a version of a character that is optically correct for the size at which it will be viewed on PDF file.
- Checking **Do not show this dialog again** and then clicking **OK** can not be displayed the **Confirmation** dialog box.
- 7 When you want to continue printing, click **OK**.

4. Names and Functions


When you start this utility, the window below appears.



Name and Icon	Description
Add button	Displays the Open File dialog box. When you select a valid file, file name, file size and last update are displayed in the File Name list.
Up button	Moves order of selected files up one or down one.
Down button	Note You can also change the order by selecting a file and then dragging it to the order you want to change.
Delete button	Deletes the selected file from the list.
<u>. • • • </u>	Note You can also delete a file by selecting a file and then pressing the Del key on the keyboard.
Printer Listing	Displays the printing systems installed in the system. Select the output target printing system here.
Settings button	Displays the printing system setting dialog box.
User Printer Settings	Displays the names of setting files saved previously.
Browse button	Displays the Open File dialog box to load previously saved setting files.
About button	Displays the version and copyright of this utility.
Print button	Starts the printing process of the file displayed in the File Name list.
Close button	Exits this utility.

5. Printing System Settings

You can make frequently used settings as default.



Copies

Specifies the number of copies. The default setting is 1.

Collate

Produces the specified number of copies as complete sets of documents. The default setting is disabled (not checked).

Layout


Specifies the layout of the output. The following layouts are available: Reduce Image to Fit, Through, Catalog (Left to Right), Catalog (Right to Left), Booklet (Left Edge Binding) and Booklet (Right Edge Binding). The default setting is Reduce Image to Fit.

When you select **Reduce Image to Fit**, the image is enlarged or reduced to fit the printing area of the paper specified in **Paper Size**.


When you select **Through**, the image is printed in the same size as the original page regardless of paper size.

When you select Catalog (Left to Right), Catalog (Right to Left), Booklet (Left Edge Binding) or Booklet (Right Edge Binding), the printing order is as follows.

Catalog (Left to Right)




Catalog (Right to Left)




Note

If the page order is not in the same order as shown above, the printing results will vary.

Booklet (Left Edge Binding)



• Booklet (Right Edge Binding)



Note


Confirm the paper size and load the paper into the cassette before printing. For example, to change the booklet configured in A4 portrait into the double spread page in A3 size, load the A3 size paper. If you load the A4 paper in landscape, a single side is reduced in A5 size, and the double spread pages in A4 are printed.


Specifies the number of pages per sheet. The following value is available: **1**, **2** and **4**. The default setting is 1.

When N-up settings 2 or 4 are used, the page layouts are as follows.


N-up


2-up





4-up





Note

If you select Through in Layout, the value of N-up is fixed at 1 and cannot be changed. Furthermore, if you select Catalog or Booklet, the value is fixed at 2 and cannot be changed.

Paper Size

Specifies the paper size applied to the output. The following

paper sizes are available:

16K, 8K, A3, A4, A5, A6, Auto, B4, B5, B6, C4, Envelope #10, Envelope #6, Envelope #9, Envelope C5, Envelope DL, Executive, Folio, Hagaki, ISO B5, Ledger, Legal, Letter, Monarch, Oficio II, OufukuHagaki, Statement, Youkei 2 and

Youkei 4. The default setting is Auto.

Duplex

Sets 2-sided printing. The following modes are available: Off, Flip on Long Edge and Flip on Short Edge. The default setting is Off.

If you select Catalog or Booklet in Layout, the value of Duplex is fixed at the Flip on Short Edge and cannot be changed.

This utility does not automatically recognize whether or not a duplex printing unit is present in a printing system. Therefore, there is a possibility that the duplex printing settings set here may be invalid.

Resolution

Specifies the printing resolution. The following resolutions are available: 300, 600, Fast 1200 and Fine 1200. The default setting is 600.

EcoPrint

Enables the printing system to reduce the amount of toner consumption to save printing costs. The default setting is disabled (not checked).

Save The Settings

Saves settings in a file.


When checked, click **OK** to save the settings. You can select the saved file by Load Setting File in the main window. The default setting is disabled (not checked)

Detailed Settings

Displays another dialog box to perform more detailed settings. Information on using the **Detailed Settings** dialog box can be found on the following page

6. Detailed Settings

You can make select media type, media source and other detailed settings in this dialog box.



Print All Pages

Check to print all pages.

If you remove this check, the range entry boxes are active. Specify the page range for printing.

Note

If you select **Catalog** in **Layout** of the **Settings** dialog box, **Print All Pages** is automatically checked and cannot be changed.

Media Type

Selects the media type used for printing. The following media types are available: Auto, Plain, Transparency, Preprinted, Labels, Bond, Recycled, Vellum, Rough, Letterhead, Color, Prepunched, Envelope, Cardstock, Coated, 2nd Side, Thick, High Quality and Custom 1 (to 8). The default setting is Auto.

Media Source

Specifies the paper supply cassette. The following media sources are available: Auto, Multi Purpose Tray, Cassette1, Cassette2, Cassette3, Cassette4, Cassette5, Cassette6 and Envelope Feeder. The default setting is Auto.

Note

The setting may be ignored depending on the configuration of the printing system. **Output to**

Specifies the paper output destination. The following destinations are available: Auto, Face Up Tray, Face Down Tray, Finisher Tray (Face Down) and VMB. The default setting is Auto.

Note

The setting may be ignored depending on the configuration of the printing system.

VMB

Quality

(Virtual MailBox)

This is active when **VMB** is specified as the **Output to** destination above. **Virtual Mailbox** feature, mailboxes created on the hard disk are assigned to multiple users. Jobs posted to a virtual mailbox can be printed later from the operation panel of the printing system.

Number: specifies the mailbox by the number. the number should be 1 to 255.

Name: specifies the mailbox by the name.

Note

The setting may be ignored depending on the configuration of the printing system.

Fold Folds copies for booklet format. The default setting is disabled

(not checked).

Staple Staples each copy set. The default setting is disabled (not

checked).

When this item is enabled, the combo box is active allowing you to select that result. The following staple positions are

available: Back, Booklet and Front.

Punch Makes copies hole punched. The default setting is disabled

(not checked).

When this item is enabled, the combo box is active allowing you to select that result. The following value are available:

Main Punch Unit and Sub Punch Unit.

Note

The setting may be ignored depending on the configuration of

the printing system.

PDF Password Enter the password required to print encrypted PDF files. The

password should be 32 characters maximum.

You can choose the printing quality, from **High Quality** to **High Speed**. Move the slider to the left to select a **High Speed** or to the right to select a **High Quality**. The default setting is center.

Note

The setting is enabled only when the PDF file to print is PDF version 1.4 or later file and using Transparency Flattenering function. Otherwise the setting is ignored.

PDF version can be confirmed on the window displayed by which selecting from File menu > Document Properties > Summary.

Transparency Flattenering function can be confimed on the Advanced Print Setup dialog box.

Network Tool for Direct Printing


Job Log

Maintains a log in the system that indicates printed PDF files and the date/time of printing. Entering a check mark for this item enables the Job Log.

For details on the Job Log, refer to the Operation Guide of the printing system.

Authentication

Displays Authentication dialog box.



User Login

To use user login function, click **User Login** to check. For details on user login function, refer to *Operation Guide* of the printing system. Select **Use Specific User ID** when always printing with same ID. Select **Prompt for User ID** when printing with several different IDs. This prompt you to enter the **User ID** and **Password** at each time you print on the printing system.

Job Accounting

To use job accounting function, click Job Accounting to check. For details on job accounting, refer to *Operation Guide* of the printing system. Select **Use Specific Account ID** when always printing with same ID. Select **Prompt for Account ID** when printing with several different IDs. This prompt you to enter the **Account ID** at each time you print on the printing system.

Default Settings

Returns all settings to their initial state.

DIRECTIVE 2002/96/CE ON THE TREATMENT, COLLECTION, RECYCLING AND DISPOSAL OF ELECTRIC AND ELECTRONIC DEVICES AND THEIR COMPONENTS

INFORMATION

1. FOR COUNTRIES IN THE EUROPEAN UNION (EU)

The disposal of electric and electronic devices as solid urban waste is strictly prohibited: it must be collected separately.

The dumping of these devices at unequipped and unauthorized places may have hazardous effects on health and the environment.

Offenders will be subjected to the penalties and measures laid down by the law.

To dispose of our devices correctly:

- a) Contact the Local Authorities, who will give you the practical information you need and the instructions for handling the waste correctly, for example: location and times of the waste collection centres, etc.
- b) When you purchase a new device of ours, give a used device similar to the one purchased to our dealer for disposal.

The crossed dustbin symbol on the device means that:



- when it to be disposed of, the device is to be taken to the equipped waste collection centres and is to be handled separately from urban waste;
- The producer guarantees the activation of the treatment, collection, recycling and disposal procedures in accordance with Directive 2002/96/CE (and subsequent amendments).

2. FOR OTHER COUNTRIES (NOT IN THE EU)

The treatment, collection, recycling and disposal of electric and electronic devices will be carried out in accordance with the laws in force in the country in question.